

# Incounter crockery dispenser, heated

P/N: 0162542 | EBR-TAS/H 100-150

**HUPFER**  
we make work flow



*Similar to illustration, technical modifications reserved. Without decoration.*

## Technical data

<b>Capacity:</b>	bis zu 98 Teile o. Haube, 104 m. Haube
<b>Payload:</b>	46 kg
<b>Capacity:</b>	600 W
<b>Supply voltage:</b>	AC 220-230 V
<b>Nominal current:</b>	2.60 A
<b>Frequency:</b>	50-60 Hz
<b>Weight:</b>	19.16 kg
<b>Width:</b>	470 mm
<b>Depth:</b>	470 mm
<b>Height:</b>	820 mm

Cup dispenser for installation into a worktop, for storing three to eight stacks of round  $\varnothing$  3.9-5.9" (100-150 mm) cups, glasses and mugs in a statically heated stacking compartment.

Dispenser in robust and hygienic design, made of high-quality stainless steel. Design for installation from above with shelf frame. Stacking compartment with stainless steel stacking platform and inner compartment panelling made of anodised-aluminium perforated plate to prevent crockery discolourations. Consistent output height thanks to manually adjustable stainless steel tension spring system. Easy cleaning of stacking compartment from above and via a cleaning opening in the base plate. Reduced temperature losses and heating time thanks to cover hood made of polycarbonate with 3-point locking mechanism. Heating through stainless steel tubular heating element, infinitely variable using thermostat toggle switch on the equipment, with temperature limiter as per VDE. Current supply via a connecting cable set consisting of two connecting cables with earthed plug and equipment plug and an On/Off switch with integrated indicator light as disconnecter.

The Hupfer incounter plate dispenser EBR-TAS/H 100-150 is used to save space when storing and handing out cups, glasses and mugs without using baskets by means of three to eight self-guided stacks on one stacking platform. The use of non-rusting stainless steel springs that are easy to insert and remove results in optimal adjustment options for different loads. The on/off switch can be conveniently integrated into the worktop and requires a cut-out measuring  $30 \times 22$  mm.

Time and date of the request: 05.04.2026, 06:14:09 *All information / dimensions are approximate, technical changes reserved. © Hupfer*